

Clutch Application and Belt Guide

Standard Shockwave		
Bore & Stroke	Flyweights	Spring
LO206	TT-10	Dark Blue
Stock Bore/Stroke	A-10-22g	Orange
Stage 4	A-10-24g	Orange
Stage 6 (lite)	A-10-24g	Orange
Stage 6 (fast)	A-10-26g	Orange
Stage 8	A-10-26g	Orange
Stage 9	A-10-28g	Orange
3 ¼ x 3	Not Recommended	
3 ½ x3		
3 ½ x3 Fast		
3¾ x3		

Shockwave (3/4")	Center Distance*
34579	6 1/8
34580	6 7/8
34581	7 3/8
34582	7 7/8
34583	8 3/8
34584	9
34585	9 1/4
Shockwave Overdrive (7/8")	
78783	8 1/16
78784	8 1/2
78785	9 1/8
* Center distances are approximated.	

Shockwave O/D (NEVER INSTALL A-10 ARMS IN O/D)			
Bore & Stroke	Flyweights	Spring	Elevation**
LO206	Not Recommended		
Raptor			
Stage 6			
Stage 8	H-1-28g	Red	Higher Elv.
	H-1-30g	Red	Lower Elv.
Stage 9	H-1-28g	Red	Higher Elv.
	H-1-30g	Red	Lower Elv.
	C-4-32g	Purple	Lower Elv.
3¼x3	H-1-30g	Red	Higher Elv.
	H-1-32g	Red	Lower Elv.
	C-4-36g	Purple	Higher Elv.
	C-4-38g	Purple	Lower Elv.
3 ½x3	H-1-32g	Red	Higher Elv.
	H-1-35g	Red	Lower Elv.
	C-4-38g	Purple	Higher Elv.
	C-4-40g	Purple	Lower Elv.
3 ½x3 Fast	H-1-35g	Red	Higher Elv.
	H-1-37g	Red	Lower Elv.
	C-4-39g	Purple	Higher Elv.
	C-4-42g	Purple	Lower Elv.
3¾x3	H-1-35g	Red	Higher Elv.
	H-1-37g	Red	Lower Elv.
	C-4-42g	Purple	Higher Elv.
	C-4-44g	Purple	Lower Elv.

4/15/16 Edition. ** Real elevation NOT D.A.

2123 C 2nd Avenue, Greeley, CO 80631
 (970) 336-5930 www.jracecar.com

